

## STUD WELDING PRODUCTS, INC

## CAPACITOR DISCHARGE (CD) 1/4" WELDERS

will shoot studs up to 1/4" in diameter











FEATURES	CDi 502	StudPro 2500Xi	CDi 1502	Pegasar 500	Lynx4 Quickshot
DESCRIPTION	Entry level. Easy to use with pre-programmed settings.	Intuitive touchscreen with preset values. Adjustable settings perfect for your needs. Our most popular CD welder.	German made with efficient inverter capacitor charging technology	Battery powered, light weight and easy to use. Inverter technology for quick recharg- ing times	Comes with a portable carring case, New and improved charging technology.
WELD RANGE	#4 to 1/4"	#4 to 1/4"	#4 to 1/4"	#4 to 1/4"	#4 to 1/4"
DUTY CYCLE	1/4"= 10 Studs/Min	1/4"= 18 Studs/Min	1/4''= 14 Studs/Min	1/4"= 20 Studs/Min	1/4''= 8 Sstuds/Min
CAPACITANCE	100,000 μF	76,000 μF	66,000 μF	100,000 μF	54,000 μF
PRIMARY POWER	100V to 240V 50/60Hz, 10a	110 VAC @ 50/60 Hz 15 AMP 220 VAC @50/60 HZz 7.5 AMP	115V 50/60Hz 10A	100V TO 240V, 50/60 Hz In Battery operation: 25.55V	100V TO 240V, 50/60 Hz 15amp
CHARGE VOLTAGE	50-100 V	35-200 V	220 V	50 to 100 V stepless voltage regulation	50-200 V
SIZE	14"L x 6"W x 10"H	14" L X 11"W X 11"H	16"L x 8"W x 10"H	18"L x 11"W x 14"H	12"L x 12"W x 5"h
POWER UNIT WEIGHT	22 lbs	18 lbs	31 lbs	26 lbs with Battery 24 lbs without Battery	24 lbs
GUN CABLE LENGTH	#2 x 10'	#4 x 25'	#2 x 21'	#2 x 10'	#2 x 10'
GROUND CABLE LENGTH	#2 x 8' single	#4 X 15' double	#2 x 8' double	#2 x 8' single	#2 x 10' double